44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

SECTION 1: IDENTIFICATION OF THE PRODUCT/COMPANY/UNDERTAKING.

1.1) Identification of the Product: Acetic acid

1.2) Synonyms: Acetic acid, methane carboxylic acid; ethanoic acid

1.3) U. N. No.: 2789

1.4) Molecular Weight: 60.051.5) Chemical Formula: CH3COOH

1.6) Identification of The Company/Undertaking

Manufacturer/supplier

INDIGO CHEMICALS

44/1, PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA-CHORASI, Surat, Gujarat, 394510

1.7) Emergency Contact Details.

INDIGO CHEMICALS

Tel: +91 76009 55231, +91 76009 55268 Email: sales@indigochemicals.com Website: www.indigochemicals.com

SECTION 2: HAZARD IDENTIFICATION

Potential Acute Health Effects:

Very hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator), of eye contact (corrosive). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation.

CARCINOGENIC EFFECTS: Not available.

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast.

TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available.

The substance may be toxic to kidneys, mucous membranes, skin, teeth. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS#	% by Weight
Acetic acid	64-19-7	100

Toxicological Data on Ingredients: Acetic acid: ORAL (LD50): Acute: 3310 mg/kg [Rat].4960 mg/kg [Mouse]. 3530 mg/kg [Rat]. DERMAL (LD50): Acute: 1060 mg/kg [Rabbit]. VAPOR (LC50): Acute: 5620 ppm 1 hours [Mouse].

SECTION 4: FIRST-AID MEASURES

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Getmedical attention immediately.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providingaid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Serious Ingestion: Not available.

SECTION 5: FIRE- FIGHTING MEASURES

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 463°C (865.4°F)

Flash Points: CLOSED CUP: 39°C (102.2°F). OPEN CUP: 43°C (109.4°F).

Flammable Limits: LOWER: 4% UPPER: 19.9%

Products of Combustion: These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances:

Flammable in presence of open flames and sparks, of heat. Slightly flammable to flammable inpresence of oxidizing materials, of metals.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Slightly explosive in presence of oxidizing materials.

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol, foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or

Special Remarks on Fire Hazards:

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

Reacts with metals to produces flammable hydrogen gas. It will ignite on contact with potassium-tart butoxide. A mixture of ammonium nitrate and acetic acid ignites when warmed, especially if warmed.

Special Remarks on Explosion Hazards:

Acetic acid vapors may form explosive mixtures with air. Reactions between acetic acid and the following materials are potentially explosive: 5-azidotetrazole, bromine pentafluoride, chromiumtrioxide, hydrogen peroxide, potassium permanganate, sodium peroxide, and phosphorus trichloride. Dilute acetic acid and dilute hydrogen can undergo an exothermic reaction if heated, forming peracetic acid which is explosive at 110 degrees C. Reaction between chlorine trifluoride and acetic acid are very violent, sometimes explosive.

SECTION 6: ACCIDENTAL RELEASE MEASURE.

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: Neutralize the residue with a dilute solution of sodium carbonate.

Large Spill:

Flammable liquid. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. If the product is in its solid form: Use a shovel to put the material into a convenient waste disposal container. If the product is in its liquid form: Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of sodium carbonate. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

SECTION 7: HANDLING AND STORAGE.

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, metals, acids, alkalis.

Storage:

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

SECTION 7: HANDLING AND STORAGE.

7.1) Precautions for safe handling.

Wear all the necessary personal protective equipment for safe handling of the product. Cover eyes, skin and mouth/nose for minimizing the exposure as advised in section 8. Handle the product using dry plastic tools. Don't add water into the product, add product to large quantities of water only. Do not mix it with any other chemicals. Eating, drinking, smoking is prohibited in the storage area. Thoroughly wash hands, eyes and contacted surface after use.

7.2) Conditions of Safe Storage, Including Any Incompatibilities.

Store it in cool, dry, well-ventilated place. Avoid direct sunlight. Keep out of the reach of children. Avoid storage around flammable chemicals and away from electrical equipment that can cause spark. Store only in original containers. Keep the container tightly closed to minimize the release of substance to the environment. Re-tie the liner bag inside the container after each use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Synthetic apron. Vapor respirator. Be sure to use an approved/certified respiratoror equivalent. Gloves/ (impervious).

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 10 STEL: 15 (ppm) [Australia] TWA: 25 STEL: 27 (mg/m3) [Australia] TWA: 10 STEL: 15 (ppm) from NIOSH TWA: 25 STEL: 37 (mg/m3) from NIOSH TWA: 10 STEL: 15 (ppm) [Canada] TWA: 26 STEL: 39 (mg/m3) [Canada] TWA: 25 STEL: 37 (mg/m3) TWA: 10 STEL:

15 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 10 (ppm) from OSHA (PEL) [United States] TWA: 25 (mg/m3) from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES AND SAFETY CHARACTERISTICS.

Physical state and appearance: Liquid Odor: Pungent, vinegar-like, sour (strong)

Taste: Vinegar, sour (strong)
Molecular Weight: 60.05 g/mole
Color: Colorless. Clear (Light)
pH (1% solution/water): 2 [Acidic]
Boiling Point: 118.1°C (244.6°F)
Melting Point: 16.6°C (61.9°F)

Critical Temperature: 321.67°C (611°F) Specific Gravity: 1.049 (Water = 1) Vapor Pressure: 1.5 kPa (@ 20°C) Vapor Density: 2.07 (Air = 1) Volatility: Not available

Odor Threshold: 0.48 ppm

Water/Oil Dist. Coeff.: The product is more soluble in water; log(oil/water) = -0.2

Ionicity (in Water): Not available

Dispersion Properties: See solubility in water, diethyl ether, acetone.

Solubility: Easily soluble in cold water, hot water. Soluble in diethyl ether, acetone. Miscible with Glycerol, alcohol,

Benzene, Carbon Tetrachloride. Practically insoluble in Carbon Disulfide.

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

SECTION 10: STABILITY AND REACTIVITY.

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, ignition sources, incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents, reducing agents, metals, acids, alkalis.

Corrosivity:

Highly corrosive in presence of stainless steel (304). Slightly corrosive in presence of aluminum, of copper. Non-corrosive in presence of stainless steel (316).

Special Remarks on Reactivity:

Reacts violently with strong oxidizing agents, acetaldehyde, and acetic anhydride. Material can react with metals, strong bases, amines, carbonates, hydroxides, phosphates, many oxides, cyanides, sulfides, chromic acid, nitric acid, hydrogen peroxide, carbonates. ammonium nitrate, ammonium thiosulfate, chlorine trifluoride, chlorosulfonic acid, perchloric acid, permanganates, xylene, oleum, potassium hydroxide, sodium hydroxide, phosphorus isocyanate, ethylenediamine, ethylene imine.

Special Remarks on Corrosivity: Moderate corrosive effect on bronze. No corrosion data onbrass

Polymerization: Will not occur.

SECTION 11: TOXICOLOGY INFORMATION.

Routes of Entry:

Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A

4-HOUR EXPOSURE. Acute oral toxicity (LD50): 3310 mg/kg [Rat]. Acute dermal toxicity (LD50): 1060 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 5620 1 hours [Mouse].

Chronic Effects on Humans:

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteriaand/or yeast. May cause damage to the following organs: kidneys, mucous membranes, skin, teeth.

Other Toxic Effects on Humans:

Extremely hazardous in case of inhalation (lung corrosive). Very hazardous in case of skin contact (irritant), of ingestion, Hazardous in case of skin contact (corrosive, permeator), of eye contact (corrosive).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May affect genetic material and may cause reproductive effects based on animal data. No human data found.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: Extremely irritating and corrosive. Causes skin irritation (reddening and itching, inflammation). May cause blistering, tissue damage and burns.

Eyes: Extremely irritating and corrosive. Causes eye irritation, lacrimation, redness, and pain. May cause burns, blurred vision, conjunctivitis, conjunctival and corneal destruction and permanent injury. Inhalation: Causes severe respiratory tract irritation. Affects the sense organs (nose, ear, eye, taste), and blood. May cause chemical pneumonitis, bronchitis, and pulmonary edema. Severe exposure may result in lung tissue damage and corrosion (ulceration) of the mucous membranes. Inhalation may also cause rhinitis, sneezing, coughing, oppressive feeling in the chest or chest pain, dyspnea, wheezing, tachypnea, cyanosis, salivation, nausea, giddiness, muscular weakness. Ingestion: Moderately toxic. Corrosive. Causes gastrointestinal tract irritation (burning and pain of the mouth, throat, and abdomen, coughing, ulceration, bleeding, nausea, abdominal spasms, vomiting, hematemesis, diarrhea. May Also affect the liver (impaired liver function), behavior (convulsions, giddines, muscular weakness), and the urinary system - kidneys (Hematuria, Albuminuria, Nephrosis, acute renal failure, acute tubular necrosis). May also cause dyspnea or asphyxia. May also lead to shock, coma and death. Chronic Potential Health Effects: Chronic exposure via ingestion may cause blackening or erosion of the teeth and jaw necrosis, pharyngitis, and gastritis. It may also behavior (similar to acute ingestion), and metabolism (weight loss). Chronic exposure via inhalation may cause asthma and/or bronchitis with cough,

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

phlegm, and/or shortness of breath. It may also affect the blood (decreased leukocyte count), and urinary system (kidneys). Repeatedor prolonged skin contact may cause thickening, blackening, and cracking of the skin.

SECTION 12: ECOLOGICAL INFORMATION.

Ecotoxicity:

Ecotoxicity in water (LC50): 423 mg/l 24 hours [Fish (Goldfish)]. 88 ppm 96 hours [Fish(fathead minnow)]. 75 ppm 96 hours [Fish (bluegill sunfish)]. >100 ppm 96 hours [Daphnia].

BOD5 and COD: BOD-5: 0.34-0.88 g oxygen/g

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long termdegradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS.

Correctly incinerated material will decompose to carbon dioxide and water only. Landfill after ensuring that material is no longer reactive and has been neutralized. Labels should not be removed before cleaning the containers. Empty containers may contain hazardous residues. Contaminated containers should not be treated as household waste. Containers should be cleanedby appropriate method and then disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Treat the contaminated water used for spillage control or used for dilution or for firefighting.

SECTION 14: TRANSPORT INFORMATION.

DOT Classification: CLASS 3: Flammable liquid. Class 8: Corrosive material

Identification: Acetic Acid, Glacial UNNA: 2789 PG: II

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information Federal and State

Regulations:

New York release reporting list: Acetic acid Rhode Island RTK hazardous substances: Acetic acid Pennsylvania RTK: Acetic acid Florida: Acetic acid Minnesota: Acetic acid Massachusetts RTK: Acetic acid New Jersey: Acetic acid California Director's List of Hazardous Substances (8 CCR 339): Acetic acid TSCA 8(b) inventory: Acetic acidCERCLA: Hazardous substances.: Acetic acid: 5000 lbs. (2268 kg)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). CLASS E: Corrosive liquid.

DSCL (EEC):

R10- Flammable. R35- Causes severe burns. S23- Do not breathe gas/fumes/vapour/spray [***] S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

HMIS (U.S.A.):

Health Hazard: 3 Fire Hazard: 2 Reactivity: 0

Personal Protection: H

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 2 Reactivity: 0

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID

Specific hazard:

Protective Equipment:

Gloves (impervious). Synthetic apron. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash googles.

SECTION 16: OTHER INFORMATION.

Source of data: United Nations Publications. (2019). *Globally Harmonized System of Classification and Labelling of Chemicals (GHS)* (Eighth Revised ed.). United Nations.

Chlorine | NIOSH | CDC. (2018). Https://www.Cdc.Gov/Niosh/Topics/Chlorine/. https://www.cdc.gov/niosh/topics/chlorine/

Disclaimer:

The safety data sheet is prepared by Indigo Chemicals to the best of its knowledge. All the information present in the SDS is obtained from verified technical sources and verified literature source to the best knowledge at the date of issue. Indigo Chemicals cannot control or foresee on how the product is used. Everyone accessing the product must be aware about the risks and take required precautions to use the material. Indigo Chemicals shall be responsible for damage caused to the consumer in terms to handling, storing, disposing and using the product. Contact Indigo Chemicals for any information regarding the SDS. The SDS applies to the direct users of the product. The SDS shall be considered valid if the product is used formixing other substances or chemicals.

Issue date: 1/2/2020

Version: 1ST.

END OF SDS

44/1 PLOT NO.50, AT PO-BHATHA, VILLAGE-BHATHA, TALUKA CHORASI, SURAT, GUJARAT-394510



SAFETY DATA SHEET: ACETIC ACID